

AirKing®

Ventilation Products

SPECIFICATIONS

ASLC50

EXHAUST FANS

50 CFM/3.0 SONES @ 0.10" WG. -HVI CERTIFIED
120 Volts, 1.4 amps, 60 Hz.

• Grill

White polymeric grill secured in place via screw mounting through the light housing, dimensions - 11" x 10 1/2".

• Light Lens

High impact polycarbonate lens, secured in position using integral tabs; easily removed if necessary.

• Light Housing

Heavy gauge cold rolled steel c/w baked enamel finish; locks in place on the grill via two integral tabs.

• Blower Wheel

One piece polymeric wheel, 4 1/2" diameter, 1" wide, with 10 fins.

• Motor

Single coil plug-in, two pole motor, life time lubrication, thermally protected. Rated 120 volts, 60 Hz., 1.4 amps.

• Fan Housing


23 ga. Galvanized metal housing, dimensions 7 3/8" x 7 5/8" x 5 7/8", double metal thickness mounting tabs.

• Duct Collar

Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.

• Lighting

100 watt maximum, type A19, medium base bulb.



CUL/HVI

Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.

• Unit Mounting

Rated Type IC for ceilings insulated to R-40. Designed to mount in ceilings with at least 6" of clearance. The unit will mount directly to the joist or using the supplied mounting bars with a rough in opening of 7 3/8" x 7 7/8". The housing will mount through drywall thickness up to 3/4".

• Ventilating Area

For bathrooms up to 50 sq. ft. for other rooms up to 60 sq. ft.

• Single Pack Shipping Info

Box Dim: 11 3/4" x 13 1/4" x 9 3/4"
 UPC: 0-8316225411-5
 Shipping Weight: 6 lbs.

PERFORMANCE

	Static Pressure (inches of w.g.)								HVI Sones @ .1 SP	Fan Speed RPM	Power Watts
	0	0.05	0.1	0.125	0.15	0.2	0.25	0.3			
Air Flow - CFM	55	53	50	48	47	44	39	34	3.0	2125	48

PROJECT								ARCHITECT			
LOCATION								ENGINEER			
CONTRACTOR								SUBMITTED BY			
								DATE			
FAN NUMBER	MODEL NUMBER	CFM	IN W.G.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS		



U.S.: 820 Lincoln Drive
 West Chester, Pennsylvania 19380-4466
 Tel: (610) 692-7400 • 877-304-3785
 Fax: (610) 696-8048

Canada: 110 Glidden Road
 Brampton, Ontario L6T 2J3
 Tel: (905) 456-2033
 Fax: (905) 456-1015